

Commercial Hardware Project Range 2020





milesnelson.co.nz



Founded in 1928, Miles Nelson is one of New Zealand's most trusted hardware companies and is proud to be 100% privately New Zealand owned and operated.

Based in Auckland, Miles Nelson distributes nationwide and internationally, and is well known for its quality product range, innovative design and commitment to customer service.

Miles Nelson's long history as a manufacturer, coupled with in house technical expertise and custom designed proprietary products means that our range is specifically designed and manufactured to suit the New Zealand market.

The use of quality materials coupled with a range of high quality finishes and a suite of styles makes the Miles Nelson range the ideal choice for commercial and residential projects.



Contents

Miles Nelson[®] offers a comprehensive range of commercial architectural hardware products:



How to use this brochure

- The colour coded contents on this page will direct you with the book divided into a MNC product guide followed by a MNC specification section, then other MNC hardware.
- The 'Lock Specification by function' section starts with a quick reference guide to the different lock functions. Please note that the codes in this section refer to a locks function and should **not** be used for ordering product. The next pages in the specifying section give more detailed information on lock function. The specifying section finishes with a cam and snib matrix. Pages 6-15 onwards contain all product information and product ordering codes.
- Product finishes are designated by icons with a guide on page 41.

Miles Nelson Service Guarantee

- Our people are great from our account representation to our customer service team and support staff. We make sure that we are easy to deal with and always go the extra mile to help.
- We have a technical support dedicated hotline to deal with any enquiries on a technical level (**see back cover** for contact details).
- Difot, our 'delivery in full, on time' rate is among the highest in country, so we always aim to have sufficient stock on hand.
- NZ owned and operated with a rich history dating back 90 years, Miles Nelson always listens to the customer, and values their feedback as we continually aim to improve our product offering.

The MNC5000 Series Mortice Locks by Miles Nelson®

The 5000 series locks have been engineered for strength, precision, and durability using the highest quality components inside a high purity zinc alloy pressure cast lock body. Your confidence will be reassured knowing that the MNC5000 has been tested beyond 250,000 cycles, and successfully passed the fire endurance tests as specified on the following page. It is also backed up with a 25 year warranty.

Testing Information

Fire Rating

The MNC5000 Mortice lock has been successfully tested for endurance within fire door assemblies for up to 120 minutes on E-Core doorsets and 60 minutes on Pyropanel FR board doorsets. Testing was conducted in accordance with Australian Standards AS1530.4-2014. The MNC5000 lockset did not initiate failure for the duration of the tests.

A fire resistance assessment report has also been issued for the MNC5000 Mortice lock for usage on timber fire doors. The report states that the MNC5000 is suitable for use on 30 and 60 minute timber fire doors.



Please refer to the fire symbol throughout this catalogue for fire door application door hardware.

For more information on fire ratings, please contact your Miles Nelson[®] representative or check door manufacturers approved lists.

2014 Warnsburg Aven Yor Ld 2012 4 (2014) yearway Boat Warne workson Parality Analysis Analy	Svising, Assuring,		EXOVO	Ponsors Hardware sponsors Report Issue day
Australia Postal Automic Postal Automic	DHAR Test Assessment No.	DHAR FRT 1	80343a.2 Page 1 of 3	Miles Nelson Andre Test associate
Polal Advance Dava 4202 Sundereng Soule, Victoria 3104 Australia	Test Sponsors Parasole		Issue Date 21/01/2019	VIC 3166 5 Lovell Court Alt
DHAR Test Assessmen Test Spon	1302/12 Glen Street Milsons Point, NSW 2061			
Test Spon Paraso	and		Validity Date	6 January 2025
1202/12 Gle	E Plus Building Products Pty Ltd 85-89 Tulip Street		21/11/2023	Amendment schedule
Milsons Point. ant	Cheltenham VIC 3192			Date Information about report 1/01/2019
E Plus Building F 85-89 Tu	The Fire Resistance Performa variation t	nce of E+ Doorsets with to the Door Lockset	the nominated	2020 - OSCIPTION
Cheltenhai		nsidered in this Report		Prepared Iv.
The Fire Res	INC5000 Mortice Lockset & Oval Key the referenced tests.		r leaf in lieu of the door lockset	Sumathi Cu
				Patrick of Patrick of
Etting a MNC5000 Mortice tested in the referenced tes		ced Test Reports Description	Test Standard	
E	V 0609 Single leaf Plywoo nominall	d faced E-core Doorset ly 45mm thick	AS 1530.4-1997	ire resistance post-
Test Report	Two Leaf Plywood	d faced E-core Doorset ly 45mm thick	AS 1530.4-1985	door lockset
SI 2271		al Supporting Data		re resistance performance of a Pyropanel FR Board Mini doorset with the nominated Interference of a Pyropanel FR Board Mini doorset with the nominated Interference of the second of t
Test	eference Doorset Descri	ption Test Du		Notice dead in this report
2 Test No.	Doorset nominally 46	Smm thick. 120 mil		As 1530.4.1985
	ale fire resistance test in accordance w rset on the 23 October 2018. It inc	cluded a MNC5000 Mort	tice Lockset & Oval Key 570	the second provided by the second provid
pilot doubted into 1	tted into the door leaf with JMA ons with LF4000 #90.	Hardware – Vivid Ard	chitectural large square plate	1530.4-2014
esculote				A Qual to One on a
erfitt	AUTHORITY Extra W	/arringtonfire Aus Ptv Ltd		e kaf Pyropanel FR Max doorset, nominally 38mm thick. AS 1530 4 1000
TESTING AUTHONY TESTING Address Address	PO Box 4	/arringtonfire Aus Pty Ltd 4282 DANDENONG SOUTH V 09-411 Hammond Road DAND	IC 3164	s leaf Pyropanel FR Mari doorset, nominally 38mm thick. AS 1530.41997 eff. Pyropanel FR Mari doorset, nominally 48mm thick. AS 1530.41997 eff. Pyropanel FR Mari doorset, nominally 48mm thick. AS 1530.41997
Phone Phone Phone ABN ABN		9767 1000	LIGHT 10 3173	al Supporting Information Advanced, nominally 48mm thick, AS 1530.4.1990
Email / Home + Email / Ho	me Page www.exc	ova.com		
Authoris:			Reviewed By:	Doorset description
mail i Her Authorisat	9.00	energy and	Patil Chan	Single leaf Pyropanel FR Mini doorset, 60 minutes 600
		1		e testis lacordance with Appendix B11 of AS 1530.4.2014 A5 1530.4.2014 Assembler 2019. It included a MNCS000 Monice dead laton filted into the dog lacit.
	Pius Jero	ome	Patrick Chan	e test in accordance with Appendix B11 of AS 1530.4 2014 was conducted on a pilot accember 2019. It included a MNCS000 Monice dead later filted into the door leaf.

MNC5000 Series **Wide Style Mortice Locks**



MNC5000

60mm Backset Mortice Lock

SS

- 88mm case depth
- 8mm spindle hub
- See page 20 for overall dimensions
- 41mm centre to centre rose fixings
- 51mm centre to centre diagonal fixings



MNC5000ND

60mm Backset Mortice Lock (No Hub Disc)

- Use with through spindle handle escutcheons
- 8mm open spindle hub



60mm Backset Mortice Passage Latch

Zinc diecast



MNC5100

60mm Backset Mortice Deadbolt

• Zinc diecast

• See page 21 for dimensions



MNC5000-02 SS

Universal Strike Plate

- For 5000 and 2200
- See page 27 for dimensions



60mm Backset Mortice Sliding Door Deadbolt

- Zinc diecast
- See page 24 for dimensions



MNC5100-02

Deadbolt/Sliding Lock Strike

SS

• For 5100 and 5300

• See page 27 for dimensions



MNC5000RK SS

Latchbolt Rebate Kit

• For 5000, 5409 and 5000ND

• See page 27 for dimensions



MNC5100RK



Deadbolt Rebate Kit

- For 5100
- See page 27 for dimensions


MNC2000 Series **Narrow Style Mortice Locks**



MNC2200 SS

23mm Backset Mortice Deadlatch

- 8mm spindle hub
- Lever retracts latch at 45°
- Comes with long faceplate



MNC2200E SS

28mm Backset Mortice Deadlatch

- 8mm spindle hub
- Lever retracts latch at 33°
- Comes with long faceplate




MNC2200/SFP (Aluminium Short Face Plate)

MNC2200/LFP (Stainless Steel Long Face SS Plate)

Face Plates

- For 2200 range
- Short face plate 155mmH x 25mmW
- Long face plate 254mmH x 25mmW



SS

MNC2100L (Long throw) MNC2100S (Short throw)

Mortice Deadbolt

separately (see page 9)

- Long throw 34mm bolt projection
- Short throw 21mm bolt projection
- Backset 22mm
- Includes short and long faceplates and escutcheons • Includes 2 x cams but order cylinders and turns

- MNC2200EP 28mm Backset Special **Mortice Latch**
 - Adjustable 28-29mm backset
 - Short case depth 39mm
 - 8mm through spindle
 - Lever retracts latch at 33°
 - Suits card access handle escutcheons

SS

- Non-locking lock body
- Comes with long faceplate



Mortice Hook Bolt

- 28mm bolt projection with 21mm hook reach
- 22mm Backset
- Includes short and long faceplates and escutcheons
- Includes 2 x cams but order cylinders and turns separately (see page 9)

MNC Mortice Lock Accessories

Kick Off (KO)

Kick off (KO) function adds a feature to the lock that makes it unable to be locked when the door is in the opened position. Kick off is available on any lock that incorporates an MLAAD5200-01. Turnsnib adaptor AND a "K2" cam.







MNCK2CAM

MNCAD5200-02RH



Hold Back (HB)


Hold back (HB) allows the latchbolt to be held in the opened position and the key removed. Available to order as complete with cylinder and keys or individual cams.



MNCPP5293R • Right hand



MNCPP5293L • Left hand



MNC4570HBLH-K2SCP MNC4570HBRH-K2SCP

- Includes 2 keys (C4 profile) and cam
- Available in left or right hand

Snib Adaptors

Refer to pages 28 and 29, cam and snib matrix for door function.



MNCAD5000-01LH



MNCAD5200-01



MNCAD5000-01RH



MNCAD5200-02RH



MNCAD5100-01



MNCAD5200-02LH

Oval Accessories



Oval Cylinder Cams

Refer to pages 28 and 29, Cam and Snib Matrix for door function.



MNCW2CAM








• Comes as pair for courtroom function



MNCRECAM

MNC Door Furniture

Wide Long Plate (Satin Chrome on Brass)





MNC156/90

Internal with Lever – no Cylinder Hole



MNC154/90 sc

Internal with Lever and Turn



sc


11

MNC154CLTLH/90 (Left hand) MNC154CLTRH/90

(Right hand)

Internal with lever and large turn

Note: Image shown is left hand



Round Rose and Accessories

SC

MNC Door Furniture


Narrow Style (Satin Chrome on brass)

Door Handle Specifications: Length: 185mm Width: 26mm Depth: 12.5mm CTC: 159mm Spindle: 7.6mm Screw: 70mm M4 Base Metal: Brass		
	MNC151N/90 SC	MNC155N/90 SC
	External with Lever and Cylinder Hole	External with Lever – no Cylinder Hole
		•
MNC101N SC	MNC105N SC	MNC152N/90 SC
External with Lever and Cylinder Hole	External with Lever – no Cylinder Hole	Internal with Lever and Cylinder Hole
	•	
MNC156N/90 SC	MNC154N/90 SC	
Internal with Lever –	Internal with Lever	
no Cylinder Hole	and Turn	

12

MNC Door Closers

The hydraulic 8000 series door closers are an aluminium body with a silver finish and have a 10 year warranty. Products on this page with the fire icon have been tested on a range of timber and mineral core approved fire doors. Contact Miles Nelson for more information or check door manufacturers approved lists.



Model	Dim	ension (mm)		Spacing nm)	Applicable door weight	Applicable door width		
	А	B C		D	E	(kg)	(mm)		
MNC8404BC/DA	207	55	40	50	39	60 - 85	930 – 1100		
MNC8626BC/DA	236	61	43	50	45	25 – 150	800 - 1400		

MNC Lock and Furniture Kits

Kit Code	MNCKITWL90CL/ST	MNCKITWL900F	MNCKITWL90PS	MNCKITWL90PR	MNCKITWL90PRDAR	MNCKITWL90PRDAL
Kit Description	CLASSROOM / STOREROOM KIT	OFFICE KIT	PASSAGE KIT	PRIVACY KIT	RH PRIVACY DISABLED ACCESS KIT	LH PRIVACY DISABLED ACCESS KIT
MNC5000 Refer Pg6						
MNC5409 Refer Pg6						
MNC151/90 Refer Pg10						
MNC1531/90 Refer Pg10				v J	•	•
MNC154/90 Refer Pg11		•		• - U •		
MNC154CLT/90 RH Refer Pg11					• • •	
MNC154CLT/90 LH/RH Refer Pg11						·]
MNC155/90 Refer Pg10			l			
MNC156/90 Refer Pg11	0		0			
MNCAD5200-01 Refer Pg8		and the second sec				

Kit Code	MNCKITWR90CL/ST	MNCKITWR900F	MNCKITWR90PS	MNCKITWR90PR	MNCKITWR90PRDA
Kit Description	CLASSROOM / STOREROOM ROSE KIT	ROSE OFFICE KIT	ROSE PASSAGE KIT	ROSE PRIVACY KIT	ROSE PRIVACY DISABLED ACCESS KIT
MNC5000 Refer Pg6	С. 	1		() 	ia La constante da la constante da
MNC5409 Refer Pg6			10° • • •		
MNCAD5200-01 Refer Pg8					
MNCR53/90 Refer Pg11	LI,		LL,	LL,	Ę
MNCR53CE Refer Pg11	0				
MNCR53ERIND Refer Pg11				0	0
MNCR53TS Refer Pg11					
MNCR53TSDA Refer Pg11					-0-

Order key barrel separately, see page 9.

Kit products are sent in a single outer box, designed to help door by door supply.



MNC Lock Specification by Function

How to Specify (Quick reference chart pages 18-19)


Nominate the correct backset as required - (e.g. 5 = 60mm Backset)
 Select the correct lock function - (e.g. 2 = Vestibule)
 Select sub function - Select the correct locking requirements (e.g. 00 = Cylinder & Turnsnib)
 Specify handing of lock - This is to determine the hand of the lock (e.g. RH = Right Hand)
 Specify finish - (e.g. SC = Satin Chrome)
 Options - To select additional options such as: H = Hold Back, K = Kick Off

Door Handing

In New Zealand doors are handed in accordance with British practice and the direction of opening is always viewed from the OUTSIDE. The closing face of the door is the one closing against the stop bead. Which side of the door is the outside?

- the outside of an exterior door is the street side or entry side
- the outside of a room door is the corridor side
- the outside of a cupboard or closet door is the room, corridor or hall side
- the outside of a single communicating door is the side from which the butt hinge are invisible when the door is closed.
- the outside of double communicating door is the space between the two doors.

A Right Hand Sliding Door is one which closes to the right and has the lock on the right hand edge, viewed always from the outside. Patio or Privacy locks are used on either patio or toilet doors. Operation to lock or unlock handles are either turnsnibs or outside emergency release.





MNC5000 Series 0 MNC2000 Series 2	:kset 50mm = 22/23mm = 28mm =	5 2 E2	5	
Outside Cylinder	unction Inside Turnsnib	= 00	1	FunctionNightlatch=0Deadlock=1Vestibule=2Sliding Door=3Combination=4
Cylinder Cylinder – Fixed Lever Cylinder Cylinder – Blank Cylinder	Turnsnib Cylinder Lever Blank	= 01 = 02 = 03 = 04 = 05 = 06 = 07 = 08	02	
Blank Emergency Snib Cylinder Cylinder	Blank Turnsnib Cylinder Cylinder	= 09 = 10 = 22 = 28	RH	Handing Right Hand = RH Left Hand = LH
		= SC = SS	SC	
			н	OptionsHold Back=Kick Off=Long Throw Bolt=Short Throw Bolt=S

Quick Reference Chart

Nightlatches E.F. 日月 Đ. 5001 5000 5002 5003 2000 2003 2001 2002 E2000 E2001 E2002 E2003 **Deadlocks** For further details see pages 21 04 £ 1 64 5100 5101 5102 5103 2102L 2103L 2100L 2101L 2100S 2101S 2102S 2103S

Vestibule Locks





For further details see pages 20

Sliding Doors




Combination

 5400
 5401
 5402
 5403

 2400
 2401
 2402
 2403

 E2400
 E2401
 E2402
 E2403




For further details see pages 24

For further details see pages 25-26

5000 Series Mortice Nightlatches

Deadlocking mortice nightlatches feature a latchbolt that is retracted by a series of cylinder or turnsnib configurations. The latchbolt is automatically locked when the door is closed.



Nightlatch 5000 / 2000 / E2000

Cylinder & Turnsnib

Opened by key from outside. Opened by turnsnib from inside. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.

Cylinder Nightlatch 5001 / 2001 / E2001

Single Cylinder

Opened by key from outside. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.

Communicating Door Lock 5002 / 2002 / E2002

Double Cylinder

Opened by key from either side. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.



Turnsnib

Opened by turnsnib from inside. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.



(1)

H

(R)










5100 Series Mortice Deadlocks

Deadbolts have a rectangular bolt. Deadbolts are operated by either cylinders or turnsnibs to retract the latchbolt.



Deadlock 5100 / 2100

Cylinder & Turnsnib

Opened by key from outside. Opened by turnsnib from inside. Available in left and right handing.


Lockup Shop Deadlock 5101 / 2101

Single Cylinder

Opened by key from outside. Available in left and right handing.



MNC2100L (Long throw) MNC2100S (Short throw)





Glass Door Deadbolt 5102 / 2102

Double Cylinder

Opened by key from either side. Available in left and right handing.



Exit Deadbolt 5103 / 2103


Turnsnib

Opened by turnsnib from inside. Available in left and right handing.

5200 Series Mortice Vestibule Locks

The vestibule locks are fully reversible and the function can be changed without removing the case. The auxiliary deadlatch bolt automatically locks the main bolt on closing the door. The vestibule locks always feature an inside handle to allow egress in case of emergencies.







MNC2200

MNC2200E



Vestibule or Entrance Lock 5200 / 2200 / E2200

Cylinder & Turnsnib

Latchbolt operated by handle from either side. Outside handle is locked or unlocked by inside turnsnib. Key outside retracts latchbolt only. Inside handles are always free. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.

Class Room Lock 5201 / 2201 / E2201

Single Cylinder

Latchbolt operated by handle from either side. Outside handle is locked or unlocked by key from outside. Inside handles are always free. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.

Exterior or Exit Door Lock 5202 / 2202 / E2202

Double Cylinder


Latchbolt operated by handle from either side. Outside handle is locked or unlocked by key from inside. Key outside retracts latchbolt only. Inside handles are always free. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.

Exit Door Latch 5203 / 2203 / E2203

Turnsnib

Latchbolt operated by handle from either side. Outside handle is locked by turnsnib inside. Inside handles are always free. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.






Storeroom Lock 5204 / 2204 / E2204

Single Cylinder


Key outside retracts latchbolt only. Outside handle is ridged at all times. Inside handles are always free. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.



Exit Door Latch 5207 / 2207 / E2207

No cylinder or turnsnib


Latchbolt operated by handle from inside only. No outside handle. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.



Office Lock 5205 / 2205 / E2205

Cylinder & Turnsnib


Latchbolt operated by handle from either side. Outside handle is locked or unlocked by either key from outside or turnsnib inside. Inside handles are always free. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.



Special Classroom Lock 5208PWD / 2208PWD / E2208PWD

Single Cylinder


Latchbolt operated by handles either side except when outside handle is made inoperable by the key from outside. Cylinder has dual function. When turned towards strike, cylinder unlocks outside handle. If turned further, cylinder will also retract Latchbolt. Inside handles are always free. Available in left and right handing.



Exit Door Lock 5206 / 2206 / E2206

Single Cylinder

Latchbolt operated by handle from either side. Outside handle is locked or unlocked by inside cylinder. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.



Privacy Lock 5210 / 2210 / E2210

Turnsnib & release

Latchbolt operated by handles either side. Outside handle is locked. Inside handles are always free. Has Kick Off function. Available in left and right handing.

5300 Series Mortice Sliding Door Locks

Sliding door locks are operated by either cylinder or turnsnib configuration. The deadbolt has a claw bolt that engages behind the strike plate to prevent the bolt being withdrawn while sliding the door.



MNC2300

69

00

C

0,

0

Θ

Sliding Door Deadlock 5300 / 2300

Cylinder & Turnsnib

Opened by key from outside. Opened by turnsnib from inside. Available in left and right handing.

Lock Up Shop Sliding Deadlock 5301 / 2301

Single Cylinder

Opened by key from outside. Available in left and right handing.

Sliding Glass Door Deadlock 5302 / 2302

Double Cylinder

Opened by key from either side. Available in left and right handing.

Exit Sliding Door Deadlock 5303 / 2302

Turnsnib


Opened by turnsnib from inside. Available in left and right handing.



5400 Series Mortice Combination Locks

Combination locks are fully reversible and the function can be changed without removing the case. The auxiliary deadlatch bolt automatically locks the main bolt on closing the door. The combination locks feature is the inside handle is always fixed when locked by the cylinder or snib.







MNC2200





Combination Entrance Lock 5400 / 2400 / E2400

Cylinder & Turnsnib

Latchbolt operated by handles from either side. Both handles are locked or unlocked by either key outside or turnsnib inside. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.

Entrance Door Lock 5401 / 2401 / E2401

Single Cylinder

Latchbolt operated by handles from either side. Both handles are locked or unlocked by key from outside. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.

Glass Door Lock 5402 / 2402 / E2402

Double Cylinder

Latchbolt operated by handles from either side. Both handles are locked or unlocked by key from outside or key from inside. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.


Patio Door Lock 5403 / 2403 / E2403

Turnsnib Inside

Latchbolt operated by handle from either side. Both handles are locked or unlocked by turnsnib from the inside. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.



5400 Series Mortice Combination Locks



Entrance Office Lock 2405 / E2405

Cylinder & Turnsnib

Latchbolt operated by handles from either side. Both handles are locked or unlocked by turnsnib from inside. Key outside retracts latchbolt. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.

Passage Latch 5409 / 2409 / E2409

Non-locking

Opens by handles either side at all times. Available in left and right handing.

Glass Door Lock 5422 / 2422 / E2422

Double Cylinder

Latchbolt operated by handles from either side. Both handles are locked or unlocked by key from inside. Key outside retracts latchbolt. Latchbolt automatically deadlatches when door is closed. Available in left and right handing.


Courtroom Lock 5428 / 2428 / E2428

Double Cylinder

Opened by turnsnib from inside. Available in left and right handing.


5000 Series Mortice Locks Auxilary Parts


Rebate Kits – Strike Plates






• For 5000, 5409 & 5000ND






Universal Strike Plate

MNC5000-02 • For 5000 and 2200



5000 Series Mortice Locks Cam & Snib Matrix

Note: The 2000 Series Deadlatches use the same Cams and Adaptors as this chart. The 2100 and 2300 Dead Bolts use rabbit ears Cams which are supplied with the lock.



	тU 2007	то 5208-		10 5210			1		2307		10 5303				2701 2701	 2700		TT 2403				2737		<u>то</u> 2428	
CAMS MNCK2CAM													•						•			•	•		
мисш2сам 🔊		•				•		•	•	•	•		•						•			•	•		
																			•			•			
									•	•															
MNCZ2CAM															•	•	•						•		
																								•	•
SNIB Adaptors			Ŷ																						
MNCAD5000-01RH	2																								
MNCAD5100-01							•					•													
MNCAD5200-01					•									•						•					
MNCAD5200-02RH														•					•	•					
MNCAD5200-02LH																			- - -	•					
HOLD Back MNCPP5293R																			•			•			
MNCPP5293L																									

Other Miles Nelson Products

Kick Plates



SS

SS

SS

Women

Pull

Push

503PPTW

503PULPR

503PUSPR

				1		Push Plat	e 300mm	
						• Blank (not	t engraved) push p	late
						• Suitable fo	or commercial appl	ications
				10 m		• 300mmH		
Kickplat	e 200mm						04 grade stainless	steel
• 304 g	rade stainless	steel				 Fixings su 	pplied	
• 200m						300mm	502PP300-100	S
• Suitab	le for commer	cial applications		65 10				
• Pre-d	rilled and cour	ntersunk holes						
 Stainle 	ess steel screw	/s supplied		•		Engraved	Push Plate 30)0mm
	Plate Width					 Engraved 		
Door size	Plate width	n				-	or commercial appl	ications
610mm	585mm	500KP610-200	SS	-		• 300mmH		
710mm	685mm	500KP710-200	SS			Brushed 3	i04 grade stainless	steel
760mm	735mm	500KP760-200	SS			• Fixings su	pplied	
810mm	785mm	500KP810-200	SS	PUSH		300mm	502PPENGR	s
860mm	835mm	500KP860-200	SS		1			
910mm	885mm	500KP910-200	SS			-	Pull Plate wit	'n
				PULL		Handle 30	00mm	
						 Engraved 	pull plate	
				1P		Suitable for	or commercial appl	ication
						• 300mmH		
						Brushed 3	04 grade stainless	steel
						 Fixings su 	pplied	
				4		300mm	502PPENGRH	s
					3			
ickplate	300mm					Round Sig	gn	
304 gra	nde stainless s	teel				• 'Push' sig	gn for restroom doo	ors
300mm	۱H			lici		Round 7	5mm diameter	
Suitable	e for commerc	ial applications		03			for commercial app	
Pre-dri	led and count	ersunk holes		- 1729/C737	1		304 grade stainles	s steel
Stainles	ss steel screws	supplied			1	 Fixings s 	upplied	
oor size	Plate Width					Baby Change	503PPTBC	s
10mm	585mm	501KP610-300	SS			Wheelchair Accessible	503PPTDIS	s
10mm	685mm	501KP710-300	SS			Men	503PPTM	s
50mm	735mm	501KP760-300	SS			Men/Women	503PPTM/W	

SS

SS

SS

501KP810-300

501KP860-300

501KP910-300

810mm

860mm

910mm

785mm

835mm

885mm

Hinges (All components are 304SS for the stainless hinges)





- Fixed pin
- Ball bearing hinge
- Size: 100mmH x 100mmW x 2.5mmD
- 304 grade stainless steel and brass


SS

SA

520SSH10075304S



- Fixed pin
- Ball bearing hinge
- Size: 100mmH x 100mmW x 2.5mmD
- 304 grade stainless steel





- Fast fix flush
- Fixed pin ٠
- Sinter bearing hinge
- Size: 100mmH x 70mmW x 2.5mmD
- 304 grade stainless steel







- Fast fix flush
- Fixed pin

•

- Size: 110mmH x 70mmW x 4mmD
- Aluminium

520ALU11070H



S QUALITY STAINLESS STEEL


- Size: 90mmH x 60mmW x 2mmD
- 304 grade stainless steel

• Fixed pin


520SS9060	(square)	SS
520SSH9060R	(radius)	SS

Other Miles Nelson Products

Door Accessories



Door Accessories



Other Miles Nelson Products

Door Fittings and Flush Bolts



Door Viewer

- 200 degree viewing angle
- Suits door thickness: 35mm-57mm

709SC	SC
709BR	BR



Door Magnet


- Size: 22mm x 6mm
- Countersunk fixings supplied

1 pair	332CP	СР
6 pairs	332/6CP	СР
1 pair magnet with cups	332MWC	СР



Dust Socket

- For use with flush bolts, socket bolts, neck bolts and patio bolts (up to 12mm thick bolt)
- Solid brass



For concrete



sc

Straight Flush Bolt

• Solid brass

000

n

))

- Length 150mm Bolt 9mm Throw 30mm
- Keyed alike available on request
- Supplied with 2 keys
- For extra key blanks refer page 38

Non-locking	505SC150	sc
	505SG150	SG
Locking	505SCL150	sc
	505SGL150	SG





- Forged solid brass
- Size 150mm x 25mm, Throw 18mm Rod 12mm
- Fixings supplied
- Brushed satin chrome finish







Flat Bar Flush Lever Bolt

- Forged solid brass
- Bolt is a flat bar
- Size 150mm x 25mm Throw 18mm
- Fixings supplied
- Brushed satin chrome finish

305SC150F



Non-locking	405SC150	sc
 For extra key 	/ blanks refer page 3	8
 Supplied with 	n 2 keys	
• Keyed alike a	available on request	
• Length 150m	nm Bolt 9mm Throw	30mm
• Available in s	standard non-locking	g or key locking function
 2010 DL922 		

BRASS

DESIGNED BY

sc


MILES NELSON

LIFETIME GUARANTEE

Non-locking	405SC150	sc
	405SG150	SG
Locking	405SCL150	sc
	405SGL150	SG

Flush Necked Bolt

Solid brass





sc

Socket Bolts, Necked Bolts and Cabin Hooks



Socket Bolts

- Made from seamless brass with an 8mm or 10mm rod BRASS LIFETIME GUARANTEE
- Fixings supplied

35mm	262BR0835BP	BR
	262CP0835BP	СР
	262FB0835BP	FB
	262SC0835BP	sc
50mm	262BR0850BP	BR
	262CP0850BP	СР
	262FB0850BP	FB
	262SC0850BP	sc
60mm	262BR0860BP	BR
	262CP0860BP	СР
	262FB0860BP	FB
	262SC0860BP	sc
75mm	262BR0875BP	BR
	262CP0875BP	СР
	262FB0875BP	FB
	262SC0875BP	sc
100mm	262BR08100BP	BR
	262CP08100BP	СР
	262FB08100BP	FB
	262SC08100BP	sc
	262SG08100BP	SG
150mm	262BR10150	BR
	262CP10150	СР
	262FB10150	FB
	262SC10150	sc
	262SG10150	SG
200mm	262BR10200	BR
	262CP10200	СР
	262FB10200	FB



Necked Bolts • Made from seamless brass with an 8mm or 10mm rod BRASS LIFETIME GUARANTEE • Fixings supplied 269BR0860BP BR 60mm СР 269CP0860BP 269FB0860BP FB sc 269SC0860BP BR 75mm 269BR0875BP СР 269CP0875BP 269FB0875BP FB 269SC0875BP sc 269BR08100BP BR 100mm 269CP08100BP СР 269FB08100BP FB 269SC08100BP sc 269SN08100 SN SG 269SG08100 BR 269BR10150 150mm СР 269CP10150 269FB10150 sc 269SC10150



269SN10150

269SG10150

SN

SG

Cabin Hooks - Commercial

 Super h 	neavy duty	
150mm	376SS150	SS
200mm	376SS200	SS

Cabin	Hooks	0.5
8mm c	from forged brass with or 10mm rod s supplied	BRASS
50mm	276BR0850BP	BR
	276CP0850BP	СР
	276FB0850BP	FB
	276SC0850BP	sc
75mm	276BR0875BP	BR
	276CP0875BP	СР
	276FB0875BP	FB
	276SC0875BP	sc
	276SG0875BP	SG
100mm	276BR08100BP	BR
	276CP08100BP	СР
	276FB08100BP	FB
	276SC08100BP	sc
	276SN08100	SN
	276SG08100BP	SG
	276SS100BP	SS
150mm	276BR10150	BR
	276CP10150	СР
	276FB10150	FB
	276SC10150	sc
	276SS150BP	SS
200mm	276BR10200	BR
	276CP10200	СР
	276FB10200	FB

Other Miles Nelson Products

and the second second

Bannister Brackets

Lumos® **Bannister Bracket**

The revolutionary Lumos® LED bannister bracket seamlessly blends function and design by providing lighting within a bannister or railing bracket body.

This development simplifies the installation of safety or railing illumination into one stylish bracket.

The brackets use low energy consumption LED bulbs with a life of approximately 12 years under continuous use. The light does not produce heat and is therefore safe to touch. Recommended bracket spacing is 900mm, as light coverage area at maximum height is 900mm. One transformer can power up to 16 brackets containing LEDs.

Requires the use of a Miles Nelson regulated power transformer, supplied separately. Complies with BIA acceptable solution D1/AS1. Can also be used with photosensitive sensors for night lighting.

Lumos brackets are designed and manufactured in New Zealand.

U	
	D

- Lumos[®] bannister bracket
- 12 volt LED downlight
- Very low power consumption
- Cool running •
- Adapter for flat profile rails •
- Fixings supplied •
- Base: 52mm x 50mm Wall projection: 70mm Upstand height: 80mm Overall height: 115mm

Indoor use	610SCBP	sc
Powder coated finish for outdoor use	610SCEBP	sc
Indoor use (without light)	611SCBP	sc
(whiled light)	611CP	СР
Powder coated finish for outdoor use (without light)	611SCBP	sc

SIGNED BY

ES NELSON



Lumos[®] Transformer

- 12 volt
- Each transformer can power 16 lights
- Tested to AS/NZS3108 at 25°C

612PA

- **DESIGNED BY** MILES NELSON
- Concealed fixing
- Suits square and round rails ٠
- Includes flat rail adapter .
- Fixings supplied
- Base diameter: 58mm Wall projection: 75mm 75mm Upstand height:
- Complies with BIA acceptable solution D1/S1

310SC	sc
310SG	SG
310PB	MB
310SN	SN



Includes flat rail adapter

• Base: Wall projection: Upstand height:	55mm 78mm 60mm
810SCWB1	sc
810SNWB1	SN
810SGWB	SG




810SG

SN

SG

Bannister Brackets



Bathroom Indicator Hardware

*8mm through fixing (14mm minimum hole size)



Indicator Bolt

- Zinc on alloy
- Suit doors 28-45mm thick
- Surface mounted





Indicator Bolt

- Stainless steel 304
- Suit doors 28-45mm thick
- Surface mounted





Indicator Hook

- Stainless indicator hook
- Suits 28-50mm thick
- Surface mounted with 6 fixing points

SS


- 6mm square spindle
- Suit sliding and hinged doors

790SS



Other Miles Nelson Products

Safety and Security





Window Opening Restrictor

- Suitable for aluminium windows
- Quality stainless steel construction •
- · Positive stop position

1 pair Includes packers and screws	251REST2PK	SS
2 pairs Includes packers and screws	251REST4PK	SS
20 pairs Trade box	251RESTB	SS
100 pairs Trade box	251RESTB100	SS
SUITABLE FOR L&RHAND		<u> </u>

Window Opening Restrictor for Aluminium Windows

- Restricts window opening
- Three locating positions
- Unique glide design for ease of use •
- Window can be fully opened when disengaged if required
- Powder coat finish

1 piece pack	250SCA1	sc
	250PWA1	PW
	250PBA1	MB
2 piece pack	250PWA2	PW
	250PBA2	MB
4 piece pack	250SCA4	sc
	250PWA4	PW
	250PBA4	MB

Window Opening Restrictor for Timber Windows

BR

- Restricts window opening
- Three locating positions
- Unique glide design for ease of use
- Window can be fully opened when disengaged if required
- Powder coat finish

250PWT1	PW
250SCT1	sc
250PWT2	PW
250PWT4	sc
250SCT4	sc
	2505CT1 250PWT2 250PWT4



Door Accessories



• 85mm centre spindle to centre keyway

		, ,
60mm Backset	760SS60	SS
45mm Backset	760SS45	SS



5 Lever Mortice Lock

- 58mm Backset
- Case depth 80mm/ Case height 109mm

Mortice Lock with 2 keys	716SN765	SN
5 Lever Key Blank	716KB5	
Rebate Kit for 716SN765	716SN12	SN

3 Lever Mortice Locks

- 2 keys supplied
- 54mm centre spindle to top of keyway

48mm Backset

716SSN663 Case depth 64mm/ SN Case height 103mm

SN

58mm Backset

Case depth 77mm/ 716SSN763 Case height 103mm



Rebate Kit

720SS

- Stainless steel
- Suits 760SS Mortice Lock



ss

Rebate kit (12.5mm) • For standard tubular latch (24.5mm hole)

291BR / 291CP / 291FB / 291SC



Tubular Latch • Satin Nickel finish Recessed box shield included 60mm backset MIL325 SN 70mm backset 415SN70 SN



70mm Euro Cylinder

- 6 pin
- C4 profile keyway
- Keyed alike option
- 3 keys supplied

Double cylinder	718SG70KD	SG
Cylinder and turn	717BLK70KD	MB
Cylinder and turn	717SN70KD	SN
Cylinder and turn	717SG70KD	SG



Privacy Turn Set

- Satin Nickel finish
- Projection 10mm
- Rose diameter 55mm • Use with MIL320

Round Rose MIL300



Tubular Privacy Bolt

SN

- Satin Nickel finish
- 60mm backset • Use with MIL300


MIL320





Other Miles Nelson Products

Pull Handles (All handles include nylon buffers and 12mm bushes for glass mount)







*Note: Face and striker plates only supplied as stainless steel

- Provides a secure latch with turns both sides for doors with pulls
- Corrosion resistant stainless faceplate
- Order euro cylinder separately refer page 39
- 60mm back set / 85mm centre to centre

Square	716SNSLK60	SN
	716SGSLK60	SG
	716BLKSLK60	MB
Round	716SNRLK60	SN
	716SGRLK60	SG
	716BLKRLK60	MB

Warranty Information



Products covered: All General Hardware Products including Bannister Brackets, Bathroom Fittings, Cabinet Hardware & Handles, Cabin Hooks, Door Fittings, Door Stops, Hinges, Hooks, Kickplates, Push Plates, Grab Rails, Letterbox Letters & Numbers, Neck Bolts, Security Fittings (excluding the Patio Bolts, Mini Bolts, Restrictor Stays and Security Window Stays) and Socket Bolts.

These products are warranted to be free from mechanical and workmanship defects for 5 years from the original date of purchase. If a mechanical defect occurs simply return the product together with proof of purchase to point of purchase for replacement.

Over time the surface may deteriorate if exposed to adverse atmospheric conditions caused by sea, air and weather. Finish deterioration caused by exposure to adverse atmospheric conditions or occurring from the use of paints, solvents, acid cleaners or scratching from keys is not considered a defect in the finish and is not covered by the warranty conditions.

Likewise the warranty does not cover damage caused by incorrect installation, accident, neglect or other factors over which Miles Nelson have no control and as such Miles Nelson shall not be held liable for any losses or expenses such as loss of use, damage to property or consequential damages or expenses.



Products covered: Miles Nelson Commercial Door Furniture, Miles Nelson Commercial Door Closers, Door Handles & Pulls, Restrictor Stays, Security Window Stays, Patio Bolts and Mini Bolts.

These products are warranted to be free from workmanship defects for 10 years from the original date of purchase. If a defect is detected simply return the product together with proof of purchase to the supplier for replacement. Products are designed for interior residential applications, unless otherwise stated.

Over time the surface may deteriorate if exposed to adverse atmospheric conditions caused by sea, air and weather. Finish deterioration caused by exposure to adverse atmospheric conditions or occurring from the use of ammoniated detergents, metal polishes, solvents, corrosive environments or other abrasive agents or scratching from keys is not considered a defect in the finish and as such is not covered by the warranty.

Likewise, the warranty does not cover damage caused by incorrect installation, accident, neglect or other factors over which Miles Nelson have no control and as such Miles Nelson shall not be held liable for any losses or expenses such as loss of use, damage to property or consequential damages or expenses.



Miles Nelson Manufacturing Ltd guarantees its products against defects in workmanship and materials. Should the product develop fault within its normal working life, Miles Nelson will repair or replace product of the same or equivalent product free of charge. Miles Nelson Manufacturing Ltd assumes no liability under this guarantee for the following.

- 1. Incorrect installation or failure to follow instructions.
- 2. Failure through improper maintenance or fair wear and tear.
- 3. Loss or damage costs incurred either indirect or consequential.
- 4. Cost of removal, replacement, and/or travelling time.
- 5. Any modification to the product from its original supplied operation design.
- 6. Plated finishes deterioration under some climatic conditions or chemical environment are exempt from this guarantee.

Miles Nelson Manufacturing Ltd reserves the right to determine whether or not any fault is caused by defects in workmanship or that any product is defective. Product specification and design improvement may change as a result of our continued commitment to quality, materials and development program. Consumer Guarantees act does not apply.

Warranty Information and Finishes



The lifetime warranty covers the integrity of the product(s) base material and as such the product is guaranteed to be free from material defects for the lifetime of the product.

The product finish is subject to the same conditions that apply to the 5 year warranty, as above.





There are two types of stainless steel commonly used in the hardware industry, 304 grade and 316 (marine) grade. 316 grade stainless has molybdenum as an additive that improves its resistance to pitting and corrosion and should be used when exposed to seaside conditions.

With a little bit of care you can minimise, if not prevent tea staining and get years of visual enjoyment from your stainless steel.

Tea staining can be described as: discolouration of the surface of stainless steel that does not affect the structural integrity or the longevity of the material. Tea staining of stainless steels occurs most commonly in coastal areas and becomes progressively worse the closer you get to water (note that most of New Zealand is considered a coastal area). Other factors such as pollution, higher temperatures and humidity can also increase the effect.

To prevent tea staining, perform regular maintenance – Wash regularly with clean fresh water, mild detergent and a cloth or soft brush. After washing rinse in clean water and wipe the surface dry with a soft absorbent cloth remembering to go with the grain on brushed stainless steel. Generally, you should wash your stainless steel every time you wash your windows or every three months. Do not use abrasive cleaners or a scouring pad of any type as they may cause excessive wear and dull the finish.





Project	
Address	
Contact	
Date	

Door Number	Description		ŀ	lardwar	e		Notes



Project	
Address	
Contact	
Date	_

Door Number	Description		H	lardwar	e		Notes



Project	
Address	
Contact	
Date	

Door Number	Description	Hardware							Notes



Project	
Address	
Contact	
Date	_

Door Number	Description	Hardware						Notes	





Overnight courier service available on request.

P: 0800 663 533
F: +64 9 489 5552
E: commercial@milesnelson.co.nz
PO Box: 31 043 | Milford, Auckland



Check out our project range brochures or view the full range of products visit: **milesnelson.co.nz**