



SERIES

Commercial swing door Operators

Cost effective, high performance openers for your commercial heavy duty installation

Our A series door closer units come in 2 options, with the 200 series having spring return functionality.



Strong and Robust

Drives door leaves up to 1200mm and 170kg



Smart and Stylish

Streamlined satin finish looks sharp in commercial settings



Highly Configurable

Can be managed in multiple configurations



Extremely Capable

Control and activate with vast array of wired and remote/wireless options

FOR MORE INFORMATION



jamesbull
ACCESS & SECURITY

James Bull Locksmiths

03 366 7123

workshop@jamesbull.co.nz

A-SERIES

Swing and Sliding
Commercial Door Operators



A-165SW

SWING DOOR OPERATOR

Configuration

Single Leaf 600-1200mm
Max weight <170kg

Power

AC 220V +/-10%
24V DC motor, 100W Max

Opening [*adjustable]

Opening time 0.5-30Sec*
Opening Speed 3-7Sec*
Open angle 80-100deg
Drive : Pull arm, push arm
Operating Temp : -20 - +45 degC
Relative Humidity : <85%

SPRING RETURN

A-200SW

SWING DOOR OPERATOR

Configuration

Single Leaf 600-1200mm
Max weight <170kg

Power

AC 220V +/-10%
24V DC motor, 100W Max

Opening [*adjustable]

Opening time 0.5-30Sec*
Opening Speed 3-7Sec*
Open angle 80-100deg
Drive : Pull arm, push arm
Operating Temp : -20 - +45 degC
Relative Humidity : <85%

CONFIGURATIONS



Single Leaf Door
Standard arm
Pushing
Left/Right



Single Leaf Door
Slide arm
Left or Right pull



Two Leaf Door
Two way traffic flow
Two alternate,
independent drives



Two Leaf Door
Electrically linked
Standard arm push
Slide arm pull

INCLUDED IN THE BOX

- Main operator unit
- Standard arm
- Slide arm
- Programmer module

OPTIONAL ACCESSORIES

Vast range of controls from remotes, to sensors all designed to suit access and mobility needs of users

